

LEVITON'S INDUSTRIAL SPECIFICATION GRADE LOCKING DEVICES ARE BUILT TO PROVIDE UNPARALLELED QUALITY AND SUPERIOR PERFORMANCE IN THE MOST SEVERE INDUSTRIAL SETTINGS.

- Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.
- Uncompromising industrial-grade quality for superior performance and long service life
 - All industrial locking devices feature heavy-duty, impact-resistant construction
 - Plugs and connectors accept wide range of conductors
 - Terminals clearly identified on all devices to speed and simplify wiring
 - Backed by a limited 10-year warranty
 - Certified for sale in Canada by an accredited certification body

15 A 125 V 2-POLE 3-WIRE GROUNDING

Model No.	Mfg. No.	Description	Cord Diameter"	Wire Gauge stranded	Price /Each
XA872	24W47	Wetguard Locking Plug, High Visibility Yellow EPTR Body	0.240 - 0.655	12-18	
XA873	25W47	Wetguard Locking Connector, High Visibility Yellow EPTR Body	0.240 - 0.655	12-18	

15 A 125 V 2-POLE 3-WIRE GROUNDING

Model No.	Mfg. No.	Description	Cord Diameter"	Wire Gauge stranded	Price /Each
XC172	4720-C	Black and White Locking Plug	0.245 - 0.700	10-18	
XC173	4729-C	Black and White Locking Connector	0.245 - 0.700	10-18	

PVC GROUNDING PLUG

- Moisture and chemical resistant plastic body
- Ideal for indoor and outdoor use
- 15 A, 125 V

Model No.	Description	Nema Configuration	Colour	Cord Diameter"	Wire Gauge	Price /Each
XE672	PVC Grounding Plug	5-15P	Yellow	0.245 - 0.655	16/3 to 14/3 cords	
XE673	PVC Grounding Connector	5-15R	Yellow	0.245 - 0.655	16/3 to 14/3 cords	



Nema Configuration



XA872



XA873



Nema Configuration



XC172



XC173



XE672



XE673

COMMERCIAL GRADE STRAIGHT BLADE PLUGS

Commercial Specification Grade Straight Blade Plugs and Connectors are rugged performers. They are moisture, chemical and abuse-resistant. And they're ideal for indoor and outdoor use. All of these features and benefits are common to 15 A and 20 A Commercial Specification Grade Plugs and Connectors. TPE rubber-backed plugs and connectors stand up to rough use and protect against dirt and moisture. Deep-slotted, backed-out terminal screws draw backwire clamps securely over stripped leads for maximum conductivity.


15 A 125 V 2-POLE 3-WIRE GROUNDING

Model No.	Mfg. No.	Description	Colour	Cord Diameter"	Wire Gauge stranded	Price /Each
XA778	515PV	PVC Grounding Plug	Yellow	0.245 - 0.655	No. 18-3 thru 12-3 cords	
XA779	515CV	PVC Grounding Connector	Yellow	0.245 - 0.655	No. 18-3 thru 12-3 cords	

15 A 125 V STRAIGHT BLADE PLUGS & CONNECTORS, 2-POLE, 3-WIRE GROUNDING CONNECTORS

PLUGS				CONNECTORS		
Model No.	Mfg. No.	Description	Price /Each	Model No.	Mfg. No.	Price /Each
XA780	14W47	Wetguard, High Visibility		XA781	15W47	
XA775	5256-VY	Python, High Visibility		XA776	5259-VY	
XA777	5256-VA	Python Angle, High Visibility				

Nema Configuration




XA779



XA778

Nema Configuration



XA780



XA777

CORROSION RESISTANT DEVICES

Corrosion resistant devices are specifically designed for extremely damp and corrosive environments. They offer additional corrosive resistance because the metal parts (blades, contacts, terminals and screws) are nickel-plated. They have also passed the ASTM (B117.13) 500 hour Salt Spray (Fog) Test.


- Cord clamp seats flush with body for all cable sizes from 10-3 ST to 18-3 SVT (.245"-.700"), providing positive strain relief while preventing damage to cable jacket
- Captive, brass #8 terminal screws are colour coded for easy wiring identification: green (ground), brass (hot) and silver (neutral)

15 A 125 V 2-POLE 3-WIRE GROUNDING STRAIGHT BLADE

Model No.	Mfg. No.	Description	Nema Configuration	Price /Each
XA848	52CM-66C	Straight Blade Plug, Yellow Nylon Body and Cord Clamp	5-15P	
XA849	52CM-69C	Straight Blade Connector, Yellow Nylon Body and Cord Clamp	5-15R	



Nema Configuration



5-15P

5-15R



XA848